

Top Load Commercial Washer

CTD27TSORW

9 KG

- Professional Grade Technology
- 3-Year Warranty*
- 4-Way agitator



* Limited parts and labour warranty. See warranty T&Cs for details.

GYRO BALANCING SYSTEM

Smart balance control. 3-D sensors re-balance uneven loads to maintain a steady spin and predictable cycle times.



TURBOWASH 3D

Fast, effective clean. Powerful jet spray for fast soaking, while independent tub and agitator motion give cleaner results sooner, lowering running costs.




INVERTER DIRECT DRIVE™ MOTOR

Quiet, belt-free drive. Fewer moving parts for quieter operation, low maintenance and long service life.



FRONT SERVICE PANEL

This removable panel lets you get inside the machine efficiently without the need to uninstall.



Top Load Commercial Washer

CTD27TSORW

9 KG

DRUM	
Drum Volume	103.4 L
Diameter	54.8 mm
Depth	391.8 mm
Capacity	9 kg
DIMENSIONS	
Product (WxHxD)	686 × 1045 × 721 mm
Carton (WxHxD)	740 × 1110 × 785 mm
Weight (Product/Carton)	55 kg / 62 kg
SPEED	
Wash (Motor/Pulsator)	Motor: 0–532 RPM Pulsator: 0–140 RPM
Extract (High Speed)	720 RPM
RATING	
Electric Ratings	220–240 V / 50Hz / 3 A
CONSUMPTION INDEX	
Water	IEC Max 95 L
Electricity	220–240 V / 0.4 kW
NOISE & CYCLE TIME	
Noise Level (Sound Power)	Lower than 60 dB
Program Duration (Default)	29 min
SYSTEM & CONTROL	
Inverter Direct Drive Motor	Y
Drain System	Brushless DC drain pump
Gyro Sensor	Y
Damper	4 Horizontal Friction Dampers
PROGRAMS	
Program List	Hot, Warm, Cold, Delicates, Custom PGM (OPL) (Long Key)
EXTERNAL FINISH	
Drum	Stainless Steel
CONNECTIONS	
Water Connections	3/4" Hot and Cold Water Connections
Drain Requirements	Standpipe, 50 mm diameter, height 700–1000 mm above floor level
Power Supply	240V 10amp GPO

